



Life Cycle Assessment of Cloudburst Management Plans in Adaptation to Climate Change in Copenhagen, Denmark

Brudler, Sarah; Arnbjerg-Nielsen, Karsten; Rygaard, Martin

Published in:
Book of Abstracts. DTU's Sustain Conference 2015

Publication date:
2015

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Brudler, S., Arnbjerg-Nielsen, K., & Rygaard, M. (2015). Life Cycle Assessment of Cloudburst Management Plans in Adaptation to Climate Change in Copenhagen, Denmark. In *Book of Abstracts. DTU's Sustain Conference 2015* [L-19] Technical University of Denmark.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Life Cycle Assessment of Cloudburst Management Plans in Adaptation to Climate Change in Copenhagen, Denmark

Sarah Brudler^{*1,2}, Karsten Arnbjerg-Nielsen¹, Martin Rygaard¹

1: DTU Environment; 2: VandCenter Syd

*sabr@env.dtu.dk

The environmental impacts of cloudburst management systems are assessed using Life Cycle Assessment (LCA). A terrestrial LCA approach as introduced by Loiseau et al. (2013) is first used in connection to storm water management (SWM) and tested using two different climate change adaptation strategies for a catchment in Nørrebro, Copenhagen. The catchment area is defined as the reference flow, from which different functions are derived based on the Three Points Approach, which divides rain events in different domains according to frequency (Sørup et al., 2012). This allows defining different safety targets for everyday and rare rain events, which are met by a combination of different elements that differ in the two scenarios. The “green” scenario mainly utilizes green infrastructure, local retention and infiltration, while the second “grey” solution employs underground pipes and retention basins. The environmental impacts resulting from implementing, operating and decommissioning are significantly smaller for the “green” scenario in all eight considered categories (41% down to 13% of the “grey” impacts). The main contributor in both scenarios is the generation of materials, e.g. concrete and steel, which highlights the possibility for system design optimization in order to reduce negative effects. The allocation of impacts shows that different functions of urban SWM systems affect the environment to a different extent, e.g. the management of extremely rare events has negligible impacts compared to handling events with a return period of up to ten years.




Figure 1: Normalized environmental impacts per year of the two scenarios, for eight selected midpoint categories

Loiseau, E., Roux, P., Junqua, G., Maurel, P., Bellon-Maurel, V., 2013. Adapting the LCA framework to environmental assessment in land planning. *Int. J. Life Cycle Assess.* 18, 1533–1548.

Sørup, H.J.D., Arnbjerg-Nielsen, K., Mikkelsen, P.S., Rygaard, M., 2012. Quantitative potential for rainwater use. Technical University of Denmark, Department of Environmental Engineering, Lyngby, Denmark.